



WAN OPTIMIZATION FOR A SUPERIOR USER EXPERIENCE

As the foundation of Blue Coat's Application Delivery Network (ADN), Blue Coat ProxySG appliances accelerate and secure business applications for users across the distributed enterprise. The Blue Coat ProxySG Acceleration Edition is a powerful yet flexible WAN Optimization solution for improving application performance. Deployed at both remote branches and in the network core, ProxySG appliances form a transparent, secure and fast application delivery infrastructure to improve user productivity, reduce bandwidth expense and enable key IT initiatives.

FEATURES

Acceleration

- > **Protocol Optimization:** Accelerate application performance by mitigating the penalties that latency imposes on inefficient protocols or applications originally architected for the LAN and running on the WAN
- > **Object Caching:** Dramatically accelerate web application and workflows that depend on centrally-stored files by delivering remote content locally in the branch
- > **Byte Caching:** Reduce the effects of latency, and significantly reduce bandwidth consumption for repetitive data elements, even across disparate applications, transmitted over the WAN
- > **Compression:** Reduce the effect of latency, and reduce bandwidth consumption for any compressible data transiting the WAN
- > **Bandwidth Management:** Ensure productivity by prioritizing enterprise-critical data flows over bulk-data or recreational traffic
- > **Video Optimization:** Stream splitting, video pre-population and video caching can save up to 99.99% of bandwidth
- > **Mobile User Optimization:** Productivity enhancement for mobile and home users with Blue Coat ProxyClient

Application Acceleration

Support for multiple protocols

- > HTTP, CIFS, SSL, FTP, MAPI, P2P, MMS, RTSP, QuickTime, TCP-Tunnel, DNS
- > Provide LAN-like application performance to remote users and branch offices
- > Deliver outstanding performance for streaming audio, video and other rich media applications
- > Bandwidth management on all acceleration services
- > Accelerate live and on-demand rich media, as well as SSL-encrypted traffic
- > Control encrypted traffic for all users and applications inside and outside the enterprise
- > Reduce recurring network bandwidth costs with multiple levels of compression and content caching

Performance & Reliability – SGOS

Platform highlights:

- > Secure object-based operating system with small footprint
- > High-speed caching with advanced object pipelining and adaptive refresh
- > Built-in pass-through network card, compression services, bandwidth management and SSL off loading

Network functionality including:

- > Active/Active bridging support using virtual IP addressing for failover and remote installations
- > Completely transparent when tunneling applications between appliances, maintaining IP and port information for traffic management
- > Native support for advanced clustering for near limitless scalability, without additional load balancing appliances
- > Routing configurations for gateway, route tables, RIP, DNS, and WCCP, with support for asymmetric routing of application delivery tunnels
- > Health checks performed on a forwarding host or external servers to verify status and availability of device
- > View & submit service requests via the Blue Coat management interface
- > Send snapshots (trace files) to Blue Coat Support Services for faster resolution

Manageability – Policy Processing Engine

Powerful management interface

- > Web-based management interface
- > Optional command line interface
- > Alerting via SNMP, SMTP and logging administrative events

Content Policy Language (CPL)

- > Create custom text-based policies to address unique policy requirements
- > Definable triggers and actions for policy definition

Extended Management with Director

- > Distribute, backup, restore policy files for multiple ProxySG appliances
- > Manage policies by device, group, or region
- > Job scheduling/job status reporting

Management & Control of ProxyClient

- > Configure, provision and maintain global deployment of ProxyClient
- > Upgrade client versions seamlessly with auto version detection and update

Visibility – Management Reporting

Default logging

- > HTTP, HTTPS, CIFS, MAPI, FTP, TCP-Tunnel, P2P, ICP, Windows Media, Real Media, QuickTime, DNS
- > Global log file limits and upload sizing
- > Client upload settings and scheduling

Custom logging and trace files

- > Selectable fields/text/log formats

Statistics

- > Bandwidth Gain
- > HTTP/HTTPS/FTP history
- > Streaming history
- > Resources

SNMP Support

- > Trap settings, community strings

Aggregate logs with Reporter™

- > Reporter dashboard - intuitive console that provides a "drill-able" overview of Web activity
- > 150+ pre-defined reports track user activity, security risks, and Web traffic performance
- > Secure browser access/role-based viewing
- > Provides real-time reporting with continuous log uploads from one or more ProxySGs



License Type	Acceleration Edition	Proxy Edition
CIFS acceleration	Yes	Yes
Windows Media optimization	Yes	Yes
Real Media optimization	Yes	Yes
QuickTime optimization	Yes	Yes
Adobe Flash optimization	Option	Option
Bandwidth Management	Yes	Yes
DNS proxy	Yes	Yes
HTTP acceleration	Yes	Yes
SSL acceleration	Yes	Yes
MAPI acceleration	Yes	Yes

License Type	Acceleration Edition	Proxy Edition
Telnet proxy	No	Yes
ICAP Services	No	Yes
Netegrity SiteMinder	No	Yes
Oblix COREid	No	Yes
Peer-To-Peer	No	Yes
User Authentication	No	Yes
Onbox Content Filtering (3rd Party or BCWF)	No	Yes
Offbox Content Filtering (e.g. Websense)	No	Yes
Instant Messaging (AOL, Yahoo, and MSN)	No	Free
SSL Termination/Proxy	Yes	Yes/Add-On

	SG300 Series			SG600 Series			SG810 Series			SG9000 Series		
	300-5	300-10	300-25	600-10	600-20	600-35	810-10	810-20	810-25	9000-5	9000-10	9000-20
License Capacity												
Current Users	10	50	Unlimited	100	200	Unlimited	700	1000	Unlimited	Unlimited	Unlimited	Unlimited
System												
Disk Drives	1x250GB SATA	1x250GB SATA	1x250GB SATA	1x250GB SATA	2x250GB SATA	2x250GB SATA	2x300GB SCSI Ultra 320	4x300GB SCSI Ultra 320	4x300GB SCSI Ultra 320	4x500GB SAS	8x500GB SAS	10x500GB SAS
RAM	2GB	2GB	4GB	4GB RAM	4GB RAM	4GB RAM	4GB RAM	6GB RAM	6GB RAM	4GB RAM	8GB RAM	16GB RAM
Network Interfaces	[2] integrated 1000Base-T NICs with bypass (no SSL offload) 1 integrated 100Base-T port for management	[2] integrated 1000Base-T NICs with bypass SSL Card 1 integrated 100Base-T port for management		[2] integrated 1000 Base-T NICs with bypass (1) integrated 100Base-T port for management SSL card			[2] integrated (on board) 10/100/1000 Base-T NICs 2x10/100/1000Base-T card (dual GigE with bypass) SSL card			4 x 1000 Base-T: 1xMgmt, 1xAux, 1 bridged pair (WAN & LAN) with bypass SSL Card		
Optional NICs	None			4x1000Base-T (copper) with bypass 4x1000Base-F (Fiber SX) with bypass			2x10/100/1000Base-T card (dual GigE) 2x10/100/1000Base-SX card (dual GigE Fibre) 4x10/100/1000Base-T card (quad GigE with bypass)			Quad GigE NIC Copper Quad GigE NIC Fiber Dual 10G Copper		
Physical Properties												
Enclosure	Desk, rack mountable* [*standard rack shelf required for rackmounting].			19" Rack-mountable			19" Rack-mountable			19" Rack-mountable		
Dimensions (LxWxH)	26.4cm x 21.1cm x 4.14cm (10.4in x 8.3in x 1.63in)			37.5cm x 42.8cm x 4.3cm (14.76in x 16.83in x 1.7in)			58cm x 44cm x 4.4cm (22.8in x 17.4in x 1.7in)			72.5cm X 4.27cm X 17.4cm (28.4in X 16.8in X 6.85in)		
Weight	2.6kg(5.7lb)			8.72kg(19.2lb)			14.1kg(31lb) 14.5kg(32lb) 15.4kg(34lb)			Approx. 40kg (90 lbs.)		
Operating Environment												
Power	AC power 100-240V, 50-60Hz, 0.82A-0.32A			AC power 100-240V, 50-60Hz, 2.16A-0.76A			AC power 100-240V, 50-60Hz, 6.3-3.0A			AC power 100-240V, 50-60Hz, 9.0-4.5A		
Maximum Power	65 Watts			150 Watts			375 Watts			240 Watts 315 Watts 345 Watts		
Thermal Rating	221 BTU/Hr			511.5 BTU/Hr			1280.25 BTU/Hr			819 BTU/hour typical 3300 BTU/Hr max 1075 BTU/hour typical 3300 BTU/Hr max 1177 BTU/hour typical 3300 BTU/Hr max		
Temperature	5°C to 40°C (41°F to 104°F) at sea level			5°C to 40°C (41°F to 104°F) at sea level			5°C to 35°C (41°F to 95°F)			5°C to +40°C (41°F to 104°F)		
Humidity	20 to 80% relative humidity, non-condensing			20 to 80% relative humidity, non-condensing			Less than 90% relative humidity, non-condensing			Operating: 20% to 80% relative humidity, non-condensing, Storage: 10% to 90% relative humidity, non-condensing		
Altitude	Up to 3048m (10,000ft)			Up to 3048m (10,000ft)			Up to 3048m (10,000ft)			Operating: Up to 3048 M (10,000 ft) Storage: Up to 12192 M (40,000 ft)		
Regulation												
Emissions	FCC Class A, EN55022 Class A, VCCI Class A, BSMI, CCC, C-tick, KCC											
Safety	UL 60950 -1, EN60950 -1, IEC 60950-1, CE Mark, TUV-GS, TUV-S, CCC, BSMI, GOST-R											
Standards	UL/CSA, TUV-S, BSMI, CCC, CE, GOST-R, Dictamine, C-tick, MIC											
Certifications	ICSA (SG810 only), NIAP EAL 2 (SG810 only), NIAP EAL 4+ (SG600/9000 in process) FIPS 140-2 (SG810 completed, SG600/9000 in process)											
Product Warranty	Limited, non-transferable hardware warranty for a period of one (1) year from date of shipment. BlueTouch Support contracts available for 24/7 software support and options for hardware support.											